

CARGO INFORMATION SCHEME			
Chemical name	Dielen 23	Last update	July-97
Common names		UN number	
Chemical formular		MFAG number	
Chemical family		MARPOL Annex	
Colour	Green	Annex II pollution cat.	
Odour	Unpleasent	IMO Ships type	
Own reaction		Density @ 15°C	1.0084
Reaction with water		Correction factor/°c	
Reaction other		Petroleum tables used	
Solubility with water		Melting point °c	30-40
Compatibility number		Boiling point °c	
Separate from no. (USCG)		Flash point °c	
Type of toxic test tubes		Auto-ignition point °c	
Toxicity in case of fire		Viscosity	
Fire extinguishing agent		Odour limit ppm	
Special fire procedure		Explos. limits Vol %	
Spill or leak procedure		Vapour press kPa/20	
		Vapour dens.rel to air	
SAFETY AND FIRST AID INFORMATION			
Main hazard		Health risk	
Symptoms if exposed		TLV ppm	
Personal protection aid		Is it a cancer agent	
		Is antidote available	
First aid			
Eye contact			
Skin contact			
Inhalation			
Ingestion			
CARGO HANDLING			
Coating requirements		Voyage temp. °c	50
Wall wash tests		Discharge temp. °c	
Previous cargo(es)		Preheating of tanks	
Fresh water flush		Cirkulation on voyage	
Demiwater flush		Inhibitor certificate	
Condition prior to loading	Clean and dry	Sweeping after disch.	Yes****
Remarks	Start sweeping as soon as possible	Heat adjacent	
Remarks			

TANKCLEANING - after discharge	
Prewash (not marpol)	
Ordinary bw wash	Yes, max temperature
Recirculation	
Steaming	
Removal of rob	Hand washing with low pressure / max temperature
Hand hosing/high press	
Chemicals for washing	Tanks are sprayed with gasoil a few times
SPECIAL INSTRUCTIONS	