

CARGO INFORMATION SCHEME			
Chemical name	Heavy cut alcohol c1618	Last update	July-97
Common names		UN number	
Chemical formular		MFAG number	
Chemical family		MARPOL Annex	
Colour	Clear	Annex II pollution cat.	B
Odour		IMO Ships type	
Own reaction		Density @ 15°C	0.8213
Reaction with water		Correction factor/°c	
Reaction other		Petroleum tables used	
Solubility with water		Melting point °c	
Compatibility number		Boiling point °c	
Separate from no. (USCG)		Flash point °c	
Type of toxic test tubes		Auto-ignition point °c	
Toxicity in case of fire		Viscosity	
Fire extinguishing agent		Odour limit ppm	
Special fire procedure		Explos. limits Vol %	
Spill or leak procedure		Vapour press kPa/20	
		Vapour dens.rel to air	
SAFETY AND FIRST AID INFORMATION			
Main hazard		Health risk	
Symptoms if exposed		TLV ppm	
Personal protection aid		Is it a cancer agent	
		Is antidote available	
First aid			
Eye contact			
Skin contact			
Inhalation			
Ingestion			
CARGO HANDLING			
Coating requirements		Voyage temp. °c	60-65
Wall wash tests		Discharge temp. °c	60-65
Previous cargo(es)		Preheating of tanks	
Fresh water flush		Cirkulation on voyage	
Demiwater flush		Inhibitor certificate	
Condition prior to loading	Clean and dry	Sweeping after disch.	
Remarks		Heat adjacent	
Remarks			

TANKCLEANING - after discharge	
Prewash (not marpol)	
Ordinary bw wash	4 hrs each tks
Recirculation	Yes, with strong Caustic Soda sollution at maximum temperature
Steaming	
Removal of rob	
Hand hosing/high press	
Chemicals for washing	
SPECIAL INSTRUCTIONS	
Do not over heat, the product will then b colored	