CARGO INFORMATION SCHEME						
Chemical name	Hydro Light Naptenic Distillate	Last update	juli, 1998			
Common names	Insulating Oil, Transformer Oil, Nytro 10X, 10Xt, 10	UN number				
Chemical formular		MFAG number				
Chemical family	Mineral Oils	MARPOL Annex	I			
Colour	Clear, bright < 0,5	Annex II pollution cat.				
Odour		IMO Ships type	02/03			
Own reaction	Stabel at normal conditions	Density @ 15°c	0,8788			
Reaction with water	No	Correction factor/°c				
Reaction other	Excessive heating and oxidizing agents to be avoid	Petrolum tables used	54D			
Solubility with water	Non soluble in water/ soluble in solvents	Melting point °c	-57			
Compatibility number		Boiling point °c	>250°C			
Separate from no. (USCG)		Flash point °c	>135°C			
Type of toxic test tubes		Auto-ignition point °c	>270°C			
Toxicity in case of fire	Noxious, flammable gasses at decomposition > 350°C	Viscosity	710 mm²			
Fire extinguishing agent		Odour limit ppm				
Special fire procedure		Explos. limits Vol %				
Spill or leak procedure	Oil spill granulates / Sand	Vapour press kPa/20				
		Vapour dens.rel to air				
	SAFETY AND FIRST AID INFORM	MATION				
Main hazard	At high temperature flammable vapours released	Health risk	Prolonged			
Symptoms if exposed	Defatting of skin and iritation	TLV ppm				
Personal protection aid	Protective clothinh, goggles, gloves	Is it a cancer agent	Not proved			
		Is antidote available	N/A			
	First aid		,,			
Eye contact	Rinse with plenty water					
Skin contact	Soap and plenty of water					
Inhalation	Fresh air if iritation					
Ingestion	Clean mouth out with water, drink plenty	Clean mouth out with water, drink plenty water, do not induce vomit.				
	CARGO HANDLING					
Coating requirements	Stainless steel, epoxy	Voyage temp. °c				
Wall wash tests	No	Discharge temp. °c	c			
Previous cargo(es)		Preheating of tanks				
Fresh water flush	Yes	Cirkulation on voyage				
Demiwater flush	Steam	Inhibitor certificate				
Condition prior to loading	Tanks amd lines to be absolutely free of water	Sweeping after disch.				
Remarks		Heat adjacent				

Remarks					
TANKCLEANING - after discharge					
Prewash (not marpol)					
Ordinary bw wash	Treat like lube oil washing				
Recirculation					
Steaming					
Removal of rob					
Hand hosing/high press					
Chemicals for washing					
SPECIAL INSTRUCTIONS					