

CARGO INFORMATION SCHEME			
Chemical name	Paraffin wax SX 70	Last update	07/29/97
Common names		UN number	
Chemical formular		MFAG number	
Chemical family		MARPOL Annex	II
Colour	white	Annex II pollution cat.	D
Odour	paraffin	IMO Ships type	3
Own reaction		Density @ 15°C	
Reaction with water		Correction factor/°C	
Reaction other		Petroleum tables used	
Solubility with water		Melting point °C	72
Compatibility number		Boiling point °C	
Separate from no. (USCG)		Flash point °C	
Type of toxic test tubes		Auto-ignition point °C	
Toxicity in case of fire		Viscosity	
Fire extinguishing agent		Odour limit ppm	
Special fire procedure		Explos. limits Vol %	
Spill or leak procedure		Vapour press kPa/20	
		Vapour dens.rel to air	
SAFETY AND FIRST AID INFORMATION			
Main hazard		Health risk	
Symptoms if exposed		TLV ppm	
Personal protection aid		Is it a cancer agent	
		Is antidote available	
First aid			
Eye contact			
Skin contact			
Inhalation			
Ingestion			
CARGO HANDLING			
Coating requirements		Voyage temp. °C	85-90
Wall wash tests		Discharge temp. °C	85-90
Previous cargo(es)		Preheating of tanks	yes
Fresh water flush		Cirkulation on voyage	
Demiwater flush		Inhibitor certificate	
Condition prior to loading	clean and dry	Sweeping after disch.	
Remarks		Heat adjacent	
Remarks	Important to maintain heating instruction		
TANKCLEANING - after discharge			

Prewash (not marpol)	
Ordinary bw wash	Minimum 90 deg.
Recirculation	
Steaming	Not allowed in this product
Removal of rob	Boiling water
Hand hosing/high press	
Chemicals for washing	
SPECIAL INSTRUCTIONS	
Purging with nitrogen, tanks should be hot prior to purging. Nitrogen blanket to be maintained during voyage at min 0,15 bar	